FORM PTO-1390 (REV. 10-94)	U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 1046.1213/JDH

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C 371

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5)
09/555057

INTERNATIONAL APPLICATION NO. PCT/JP 99/05202	INTERNATIONAL FILING DATE September 22, 1999	PRIORITY DATE CLAIMED September 25, 1998

TITLE OF INVENTION
INFORMATION PROCESSING APPARATUS, INFORMATION PROCESSING METHOD AND MEDIUM

APPLICANT(S) FOR DO/EO/US
(1) Takeshi KUMAZAWA (2) Nobuhito FUKUI

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. [X]   This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.

2. [ ]   This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.

3. [X]   This express request to immediately begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay the examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(I).

4. [ ]   A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.

5. [X]   A copy of the International Application as filed (35 U.S.C. 371(c)(2))
   a. [X] is transmitted herewith (required only if not transmitted by the International Bureau).
   b. [ ] has been transmitted by the International Bureau.
   c. [ ] is not required, as the application was filed in the United States Receiving Office (RO/US).

6. [X]   A translation of the International Application into English (35 U.S.C. 371(c)(2)).

7. [X]   Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
   a. [X] are transmitted herewith (required only if not transmitted by the International Bureau).
   b. [ ] have been transmitted by the International Bureau.
   c. [ ] have not been made; however, the time limited for making such amendments has NOT expired.
   d. [ ] have not been made and will not be made.

8. [ ]   A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).

9. [ ]   An oath or declaration of the inventor (35 U.S.C. 371(c)(4)).

10. [ ] A translation of the Annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. [X] An Information Disclosure Statement Under 37 CFR 1.97 and 1.98.

12. [ ] An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.

13. [ ] A FIRST preliminary amendment.
    [ ] A SECOND or SUBSEQUENT preliminary amendment.

14 [ ]   A substitute specification.

15. [ ] A change of power of attorney and/or address letter.

16. [ ] Other items or information:

U.S. Application No. (If known, see 37 CFR 1.5)	INTERNATIONAL APPLICATION NO.	ATTORNEY'S DOCKET NUMBER
09/555057	PCT/JP 99/05202	1046.1213/JDH

17. [X] The following fees are submitted:

	CALCULATIONS	PTO USE ONLY

Basic National Fee (37 CFR 1.492(a)(1)-(5)):
Search Report has been prepared by the EPO or JPO $840.00

International preliminary examination fee paid to USPTO
(37 CFR 1.482) $670.00

No International preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) $760.00

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO $970.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) $96.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

	$ 840.00	

Surcharge of **$130.00** for furnishing the oath or declaration later than [ ]20 [ ]30 months from the earliest claimed priority date (37 CFR 1.492(e)).

	$	

Claims	Number Filed	Number Extra	Rate		
Total Claims	43 -20 =	23	X $ 18.00	$ 414.00	
Independent Claims	6 - 3 =	3	X $ 78.00	$ 234.00	
Multiple dependent claim(s) (if applicable)			+ $260.00	$ .00	

TOTAL OF ABOVE CALCULATIONS =	$ 1488.00	

Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28)

	$	

SUBTOTAL =	$ 1488.00	

Processing fee of **$130.00** for furnishing the English translation later than [ ]20 [ ]30 months from the earliest claimed priority date (37 CFR 1.492(f)).   +

	$	

TOTAL NATIONAL FEE =	$ 1488.00	

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **$40.00** per property   +

	$ 0.00	

TOTAL FEES ENCLOSED =	$ 1488.00	

	Amount to be: refunded	$
	charged	$

a. [X] A check in the amount of $1488.00 to cover the above fees is enclosed.
b. [ ] Please charge my Deposit Account No. 19-3935 in the amount of $____ to cover the above fees. A duplicate copy of this sheet is enclosed.
c. [X] The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 19-3935. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO: May 19, 2000
                                                             DATE   SIGNATURE

STAAS & HALSEY
700 Eleventh Street, N.W.   James D. Halsey, Jr.
Suite 500   NAME
Washington, D.C. 20001
Telephone: (202) 434-1500   22,729
Facsimile: (202) 434-1501   REGISTRATION NUMBER

DESCRIPTION

INFORMATION PROCESSING APPARATUS, INFORMATION PROCESSING

METHOD AND MEDIUM

5   Technical Field

The present invention relates to a technology effective in an application to a method of displaying an object on a display device of a personal computer, etc..

10   Background Arts

An interface friendly to users on a display of a computer, etc. has been developed, and browsing and execution of a file and a folder are facilitated by clicking, e.g., an icon and a button by sue of a mouse.

15   On the other hand, a search for a database on the Internet becomes increasingly user-oriented, and, as represented by a search engine such as YAHOO and so on, a link is set to a header sentence of a result of search, whereby a homepage of text can be easily browsed.

20   It is, however, a situation that a user interface for displaying the information such as a file and a list of the result of search for the database in such a format the user is able to visually grasp contents thereof, is not yet actualized.

That is to say, it can be visually comprehended that the

25   icon symbolizing the file within the computer indicates what sort of document or image data, however, a data quantity and date/time of creation of the file can not be recognized unless

displayed in details.

Further, the search result through the search engine on the Internet, etc. is displayed in a data format known as HTML (Hyper Text Markup Language). This search result is, however, simply statically displayed through a browsing program called a browser on the screen, which is unsuited to such an application that the user skims through the search results on the disk top and only a necessary item of information is displayed thereon.

Further, as in case of PointCast Network which is a product of PointCast Corp., there is a system in which pieces of information such as headlines and stock prices runs in the form of [Ticker] as a telop runs and are thus displayed on the screen. The information displayed on this Ticker is linked to detailed information (which will hereinafter be referred to as link information).

According to this technology, when the link formation requiring the detailed information is displayed on the Ticker, a user selectively indicates (clicks double) the concerned link information on the ticker by use of a mouse, and thus accesses a Web site where the detailed information linked to the link information exists, whereby the detailed information can be displayed.

According to the prior art constructed such that the detailed information linked to the link information is thus displayed in response to the selective indication of the link information displayed on the ticker, the user is able to browse a desired item of detailed information by a simple operation

such as selectively indicating the information on the ticker updated in sequence.

Even when the necessary information is displayed on the ticker, however, the user is in the process of performing other operations and may not therefore display the detailed information without selectively indicating the link information. In such a case, if failing to catch a timing of that selective indication, the user has to wait for a next information display timing when a desired item of link information is displayed on the ticker.

Moreover, the ticker is updated so that the latest information is displayed and hence, if failing to catch the selective indication timing, it follows that the link information to the desired item of information is not displayed on the ticker. In this case, it is required that the user specifies a URL (Uniform Resource Locator) (Web site) to which the desired item of detailed information is related by executing other searching process and browses the information.

According to the prior art described above, it is difficult to browse the detailed information immediately when the user needs, and an operational load upon the user might increase.

It is an object of the present invention, which was devised under such circumstances, to provide an on-disk-top information display system enabling the user to visually easily grasp contents of information accumulated in a computer of the user or in a data server via a network, and capable of attaining

a method of conceptually easily acquiring the information.

Disclosure of Invention

According to a first aspect of the present invention/,

5   an object display device comprises means for converting a

representative character string of source data containing

character strings into image data defined as an object, means

for storing the source data and the image in a manner of relating

these pieces of data to each other, and means for displaying

10   the image data on display means.

The source data is, e.g., a document file and newspaper

article data obtained as a result of searching a database. A

character string serving as a main subject of the file or the

data is converted from code data into a bitmap data format.

15   The thus created image data is displayed on a display

device such as a display unit, etc..

Thus, the image data defined an object representing the

source data is displayed on the display means, whereby a content

of the source data can be grasped at a glance. This highly

20   facilitates a user's judgement as to whether details of the

source data should be browsed or not.

According to a second aspect of the present invention,

the object display device according to the first aspect of the

invention, may further comprise means for displaying the source

25   data linked to when the image data displayed is designated.

With this construction, the source data, of which the

content can be easily grasped according to the first aspect of

the invention, the image data is designated by coordinate indicating means such as a mouse, etc., thereby facilitating the browse.

According to a third aspect of the present invention, the object display device according to the first aspect of the invention, the image data is structured such that the character string is converted into a bitmap and thus laid out on an background image.

The image data is thus structured, thereby facilitating a user's visual comprehension about an object symbolizing the source data.

According to a fourth aspect of the present invention, the object display device according to the third aspect of the invention, the image data has a window, provided along a periphery of the background image, for showing an attribute of the source data to which the image data is linked.

This attribute of the source data is, for instance, a capacity of the source data, and the data may be displayed in such a way that a size of a window frame becomes different corresponding to this capacity (according to a fifth aspect of the present invention). In this case, an efficient display may be carried out by preparing beforehand template images with frame sizes being different (according to a sixth aspect of the present invention).

Further, the attribute of the source may be acquisition date and time of the source data, and the data may be displayed in a window of which a frame configuration becomes different

corresponding to the number of hours or days since the time when the source data was acquired (according to a seventh aspect of the present invention). In this case also, there may be prepared template corresponding to the number of hours or days

5 elapsed (according to a eighth aspect of the present invention).

According to a ninth aspect of the present invention, the object display device according to the first aspect of the invention, further comprises means for displaying in movement plural pieces of image data corresponding to respective pieces

10 of source data in predetermined areas. The moving display of Plural pieces of image data can be attained by ensuring the area in the frame or window in an upper portion on the disk top of the display device (display unit) of the user, and moving the image data visually right and left within this area. More

·15 specifically, when the bitmap image as the image data is displayed on the display unit, it is feasible to actualize such a visual effect that the data runs as if on an electronic bulletin board by adding or subtracting an X-coordinate value of a display position.

20 The means for thus displaying the data in movement is provided, whereby the user is able to grasp an epitome of contents of plural items of data even while executing other data processes on the disk top.

According to a tenth aspect of the present invention, the

25 object display device according to the ninth aspect of the invention, further comprises means for selecting a desired piece of image data from the image data displayed in movement,

and means for displaying the selected image data in an area excluding the display area.

When the user detects a target item of data while browsing the image data displayed in movement, the image data concerned is chosen by use of the means for selecting the image data, e.g., a coordinate indication device such as a mouse, etc. and shifted to an area other than the display area of the image data. For attaining this, an interface method such as a drag-and-drop operation and so one may be used. The image data thus selected by the user can be displayed while being ever-situated on the disk top screen of the display device.

According to an eleventh aspect of the present invention, the object display device according to the tenth aspect of the invention, further comprises means for displaying the linked source data on the display means when the image data displayed is designated.

The image data displayed in the area other than the display area according to the tenth aspect of the invention, is selected by the selecting means, whereby the source data linked to this piece of image data is displayed.

Thus, the source data defined as detailed information is easily browsed from the image data ever-situated on the disk top.

A twelfth aspect of the present invention corresponds to the first aspect, a thirteenth aspect to the second aspect, a fourteenth aspect to the fifth aspect, a fifteenth aspect to the seventh aspect, a sixteenth aspect to the ninth aspect, a

seventeenth aspect to the tenth aspect, and an eighteenth aspect to the eleventh aspect, respectively.

According to a nineteen aspect of the present invention, steps of a method according to the twelfth aspect of the invention are stored as a program on a readable-by-computer storage medium.

The storage medium herein may embrace all types of mediums having optical, magnetic and magneto-optic recording means, and includes an optical disk, a magneto-optic disk and a magnetic tape, or a cartridge, a cassette, a card which accommodate these mediums.

According to a twentieth aspect of the present invention, the program according to the thirteenth aspect is stored on the medium according to the nineteenth aspect of the invention.

According to a twenty first aspect of the invention, the object display device according to the first aspect of the invention, further comprises means for setting an effective period as attribute information with respect to the source data, the source data with an elapse over the effective period is not converted into the image data.

That is to say, the effective period is set with respect to the image data displayed on the display means, and only the latest information within a fixed period can be always browsed without an overflow of information on the screen even when new pieces of information such as news are daily added.

According to a twenty second aspect of the invention, the object display device according to the second aspect of the

invention, the previous image data is not displayed when the
source data is displayed on the display means upon the
designation of the image data.

   With this contrivance, the source data which has been once
5 browsed is not displayed as the image data, and it is therefore
feasible to prevent the once-browsed information from being
clicked again indeliberately.

Brief Description of the Drawings

10   FIG. 1 is a view showing an outline of a hardware system
in an embodiment of the present invention;

   FIG. 2 is an explanatory view showing a process of
creating bitmap data for a dynamic display in the embodiment;

   FIG. 3 is an explanatory view showing a process of
15 creating bitmap data for a static display in the embodiment;

   FIG. 4 is a view showing a standard template of a window
used in the embodiment;

   FIG. 5 is a view showing a modified template (1) of the
window used in the embodiment;

20   FIG. 6 is a view showing a modified template (2) of the
window used in the embodiment;

   FIG. 7 is a view showing a modified template (3) of the
window used in the embodiment;

   FIG. 8 is a view showing the process of creating the bitmap
25 data for the static display on a disk top screen in the
embodiment;

   FIG. 9 is a view showing a modified template (4) of the

window used in the embodiment; and

FIG. 10 is an explanatory view showing a geometry of layout on the disk top screen in the embodiment.

5 Best Mode for Carrying out the Invention

An embodiment of the present invention will hereinafter be described with reference to the drawings.

FIG. 1 shows an outline of a hardware architecture of a system for actualizing the present embodiment. The present

10 embodiment can be actualized by, specifically, an office computer of a personal computer and an application program operating on an operation system.

In FIG. 1, a display device designated by the number 1 may involve the use of a display unit of the personal computer.

15 A display control unit 2 has a function of controlling display on the display device 1, and corresponds to a display control processor, a CPU, etc. in the personal computer. A storage device 3 implies a large-capacity storage medium such as a hard disk device, etc., and is stored with text data, still picture

20 data, motion picture data, voice data and so on.

A date/time management unit 4 is a so-called timer, and what the date/time management unit 4 corresponds to is a timer for managing a date and a time when a file is created and updated in the personal computer.

25 FIG. 2 shows a flow of processes in which a display article table 8 is created from a data file 5 stored in the storage device 3, and a bitmap data 11 for dynamic display is created.

The data file 5 in the storage device 3 is stored per folder with pieces of news article information collected on the Internet in a tree structure. For example, source data as the substantial of the article is stored as text data in an HTML

5 format such as [news1.html], and image data such as [new1.gif], [news1.jpg] etc. displayed simultaneously with the text data is stored as image data in a folder named [IMG]. Further, voice information such as [nes1.wav] and so on is hierarchically stored in a folder named [SND], and motion picture data such

10 as [news1.mov], etc. is likewise stored in a folder named [MOV].

A links to each file is described by use of a tag in the HTML file defined as the source data, whereby tat item of data can be browsed as multimedia data through a browser program.

In accordance with this embodiment, the data file 5 stored

15 in such format has, together with link information described in the source data (the HTML file), information types (news, sports, etc.), information sources (such as specific newspaper publishing companies, etc.), information titles (characters subsequent to a title tag described in the source), acquisition

20 year/month/date, and information quantities as pieces of attribute information. Among those items of information, the acquisition year/month/date and the information quantity may be shared with attribute information of the file managed by the operating system.

25 According to the present embodiment, the display control unit 2 creates an article list 6a from the data file 5 (the HTML file). This article list 6a is created by combining a character

string defined as a title tag of the HTML with an epitome of the concerned article described in the data file 5 (the HTML file). Further, this article list 6a is structured of the character information.

5   Next, an article list 6a is created from another data file and merged with the previously created article list 6a, thereby creating a single display article list 7. This article list 7 is stored as a display article table 8 in the HTML format in the storage device 3.

10   Subsequently, the display control unit 2 creates bitmap data 11 for dynamic display from the display article table 8. This item of dynamic display oriented bitmap data 11 is created as rectangular bitmap data by extracting a representative character string, e.g., a character string corresponding to a headline when the concerned data item is an article on the newspaper from the data items stored in the display article table 8, and converting this extracted character string into a bitmap. At this time, the rectangular image data is prepared beforehand as a bitmap in the storage device 3, and the character string is bitmapped and thus laid out on the rectangular image, thereby creating the dynamic display oriented bitmap data 11. In this case, the rectangular image may be colored in black, while the character string may be colored in white or yellow.

      The dynamic display oriented bitmap data 11 is used for display while moving from left to right within a frame 10 displayed on the display device 1 as in the case of an electronic bulletin board. That is, in the embodiment, the dynamic display

oriented bitmap data 11 is moved in sequence within the frame 10 disposed on a disk top screen of the display device 1 under the control of the display control unit 2, thereby obtaining a visual effect as if on the electronic bulletin board. To be more specific, the dynamic display oriented bitmap data 11 is sequentially rewritten by predetermined bits in a -X axis direction within the frame 10, thereby obtaining the visual effect as if the dynamic display oriented bitmap data 11 moves from right to left.

Note that the display control unit 2 displays in movement the dynamic display oriented bitmap data 11 within the frame 10 at an interval of a predetermined time. After the dynamic display oriented bitmap data 11 has been displayed in movement within the frame 10, the display control unit 2 displays in movement the same dynamic display oriented bitmap data 11 after a predetermined time has elapsed.

Note that there may be provided an effective period of the dynamic display oriented bitmap data 11 displayed in movement within the frame 10. Such an effective period is managed by the date/time management unit 4. Then, the effective period may be set by a user, and the user is made to display an unillustrated set screen and to input the effective period. Herein, the effective period is what can be set in number of days, number of weeks, number of months, etc., and in this embodiment this period be, it is assumed, set to one day. The number of days elapsed is obtained from the acquisition year/month/date and present date information retained as

attribute information in each article list, and it is judged whether or not that number of days exceeds the set effective period. Then, the above-described creating process of the dynamic display oriented bitmap data 11 is executed by use of

5 the article list falling within only the effective period. With this process, only contents of the articles within the period desired by the user and a content of the latest article, are displayed in the frame 10, and hence the contents of the articles unnecessary to the user are not displayed with a less number

10 of article contents displayed in movement within the frame 10. It is therefore easier for the user to grasp and select the contents of the respective articles.

Next, a process in which static display oriented bitmap data 14 is created from the dynamic display oriented bitmap data

15 11 thus displayed, will be explained referring to FIG. 3.

That is, among pieces of dynamic display oriented bitmap data 11a, 11b, 11c displayed in movement within the frame 10, the specified dynamic display oriented bitmap data 11b is dragged (designated) by a mouse and dropped (the dropping

20 implies a state where a designated position as kept in the designated state is shifted, and this designation is cancelled in a specified position on the screen) onto the disk top screen, at which time the static display oriented bitmap data 14 corresponding to the dynamic display oriented bitmap data 11b

25 is created in that drop position.

FIG. 8 specifically shows how the static display oriented bitmap data 14 is created from the dynamic display oriented

bitmap data 11b on the disk top screen.

In this case, the display control unit 2, to begin with, detects designated position coordinates of the mouse dragged, and recognizes that this designated position exists in a pixel

5   region of the dynamic display oriented bitmap data 11b. then, the display control unit 2 accesses the article items of the display article table 8 linked to the dynamic display oriented bitmap data 11b. Subsequently, the representative character string, i.e., the character string corresponding to the

10   headline when the data item concerned is the article on the newspaper, is extracted from the accessed article items. The extracted character string is converted into the bitmap, thereby creating the rectangular static display oriented bitmap data 14. At this time, the static display oriented bitmap data

15   14 is created in the same procedure as when creating the dynamic display oriented bitmap data 1. Specifically, the rectangular image data is prepared beforehand as a bitmap in the storage device 3, and the character string is bitmapped and thus laid out on the rectangular image, thereby creating the static

20   display oriented bitmap data 14.

Note that the static display oriented bitmap data 14 may also be created by copying the already-created dynamic display oriented bitmap data 11 instead of creating the data 14, as discussed above, in the same procedure as the dynamic display

25   oriented bitmap data 11.

The static display oriented bitmap data 14 is structured of a display data element 13 and a window 12 arranged along its

periphery. Herein, the window 12 is stored as bitmap data in the storage device 3, however, there are prepared the windows 12 taking a plurality of configurations as templates.

5 This window 12, which is to be used, differs corresponding to an attribute of the article item in the display article table 8 to which the static display oriented bitmap data 14 to be displayed is linked. For instance, if the number of files (the HTML file, a GIF file, etc.) linked to the static display oriented bitmap data 14 is less than 5, the frame takes such

10 a configuration that, as shown in FIG. 4, the frame ahs the same thickness with respect to left and right sides, and upper and lower sides. If the number of files linked to the static display oriented bitmap data 14 is over than 5 but is not more than 9, there is used such a template that the lower side of the frame

15 is twice as thick as other sides. Hereinafter, there are used likewise the templates in which the thickness of the lower side increases three time (see FIG. 6), four times and five times (see FIG. 7), each time the number of files linked to exceeds 5.

20 With the contrivance that there are thus prepared the templates in which the thickness of the lower side varies corresponding to the number of files, the user may be given an intuition to know an estimation of the number of files linked to the static display oriented bitmap data 14 by browsing the

25 static display oriented bitmap data 14 displayed on the disk top screen on the display device 1.

The above-described variation of the lower side of the

frame 10 may, other than the case of depending on the number
of files linked to, depend upon a total capacity of the files
linked to. For example, if the total capacity of the files
linked to is 500 Kbytes or smaller, there may be used the template

5   in which, as shown in FIG. 4, the right and left sides, and the
upper and lower sides all have the same thickness. If over 50
Kbytes but less than 1 Mbytes, there may be used the template
in which the thickness of the lower side of the frame 10 is twice
those of other sides.

10   Further, if the total capacity of files is over 1 Mbytes
but less than 1.5 Mbytes, there is used the template in which
the lower side of the frame 10 has a 3-fold thickness as large
as those of other sides (FIG. 6).

           On the other hand, in addition to the templates in which

15   the thickness of the lower side of the frame 10 is made variable,
there may be prepared the template assuming such a configuration
that the right side is half rolled up. This configuration
manifests a design of what a side end of tack paper adhered to
a wall surface in a real office is, with its adhesion having

20   been decreased with an elapse of time, half rolled up.

           For instance, when the static display oriented bitmap
data 14 is laid out on the disk top screen by a drag-and-drop
initially from the frame 10, what seems standard as shown in
FIG. 4 is adopted as the window 12. If a period over seven days

25   has elapsed under the management of the date/time management
unit 4 since it was acquired, however, the window 12 is changed
to take a configuration as illustrated in FIG. 9. This enables

the user to conceptually grasp a state of time elapse since the date and time when the source data concerned was acquired, whereby the user might be prompted to access the source data quickly.

5   FIG. 10 shows an example of a geometry of layout on the disk top screen of the display device 1. As shown in FIG. 10, the fame 10 is disposed at an upper portion on the screen, and the dynamic display oriented bitmap data 11 is sequentially displayed in movement. Further, the static display oriented

10   bitmap data 14 crated by dragging and dropping any one of the dynamic display oriented bitmap data sets 14, is displayed in a left lower region on the screen. Then, when this item of static display oriented bitmap data 14 is clicked by the mouse, the data file 5 (the HTML file) linked to the static display

15   oriented bitmap data 14 concerned is opened by the browser program. Referring to FIG. 10, an area indicated by 15 is a browser-based display screen, and this screen is displayed according to a description of the data file 5.

      Note that the display control unit 2, when detecting that

20   the source data (the data file 5) linked to is displayed by designating (clicking) the static display oriented bitmap data 14, creates the display article list 7 excluding the article list of the relevant static display oriented bitmap data 14, and may create the dynamic display oriented bitmap data 11 based

25   on this updated display article list 7. The article browsed as the source data (the data file 5) is not displayed any more as the dynamic display oriented bitmap data 1 in the frame 10

on the display, thereby making it feasible to avoid repetitive browsing of the article concerned.

As discussed above, according to the present embodiment, the representative character string, e.g., the headline of the article on the newspaper, is bitmapped from the character strings of the data file 5 and displayed as the dynamic display oriented bitmap data 11, thereby facilitating a comprehension of the user by browsing.

Furthermore, with respect to the article about which the user is concerned, the static display oriented bitmap data 14 linked to the source data is created from the dynamic display oriented bitmap data 11 and laid out on the disk top screen, whereby the content of the source data concerned can be easily confirmed.

Note that the user's operation for creating the static display oriented bitmap data may not necessarily be the drag-and-drop operation as explained in the present embodiment. Namely, the mouse-used double-clicking on the dynamic display oriented bitmap data and an operation of an unillustrated dedicated button, may be used as a trigger for creating the static display oriented bitmap data. The drag-and-drop operation explained in this embodiment is, however, most suited to a sense of action of stocking a desired item of information on the disk top.

Further, the image data has been described so far as the bitmap data and may take, as a matter of course, formats other than what has been given above.

According to the present embodiment, the link information to the detailed information required by the user can be stocked in such a format that the epitome thereof is understandable, and, besides, the thus stocked link information is selectively

5   clicked, whereby the detailed information linked to can be browsed.

Accordingly, the information desired by the user can be stocked out of the information of which the display content is sequentially changed. Moreover, the detailed information

10 corresponding to the information stocked can be browsed immediately when the user needs, and it is possible to reduce an operational load upon the user.

Industrial Applicability

15 The present invention is applicable to the display of a result of the retrieval on the Internet.

WHAT IS CLAIMED IS:

1. An object display device comprising:

a converter means for converting a representative character string of source data containing character strings into image data defined as an object;

a storage means for storing the source data and the image in a manner of relating these pieces of data to each other; and

a display means for displaying the image data on display means.

2. An object display device according to claim 1, further comprising the display means for displaying the source data linked to when the image data displayed is designated.

3. An object display device according to claim 1, wherein the image data is structured such that the character string is converted into a bitmap and thus laid out on an background image.

4. An object display device according to claim 3, wherein the image data has a window, provided along a periphery of the background image, for showing an attribute of the source data to which the image data is linked.

5. An object display device according to claim 4, wherein said display means displays the image data together with the window, of which a frame size differs corresponding to a capacity of the source data to which the image data is linked.

6. An object display device according to claim 4, further comprising template images of plural types of windows, of which frame sizes are different,

5   wherein said template corresponding to a capacity of the source data is used.

7. An object display device according to claim 4, wherein said display means displays the image data together with the

10   window of which a frame configuration differs corresponding to the number of hours or days since the time when the source data to which the image data is linked was acquired.

8. An object display device according to claim 4, further

15   comprising template images of plural types of windows, of which frame configurations are different,

wherein said template corresponding to the number of hours or days since the time when the source data was acquired.

20   9. An object display device according to claim 1, further comprising the display means for displaying in movement plural pieces of image data corresponding to respective pieces of source data in predetermined areas.

25   10. An object display device according to claim 9, further comprising:

a selector means for selecting a desired piece of image

data from the image data displayed in movement; and

the display means for displaying the selected image data in an area excluding the display area.

5   11. An object display device according to claim 10, wherein the source data linked to is displayed on said display means when the image data displayed is designated.

12. An object display method comprising:

10   a step of converting a representative character string of source data containing character strings into image data defined as an object;

a step of storing the source data and the image in a manner of relating these pieces of data to each other; and

15   a step of displaying the image data on display means.

13. An object display method according to claim 12, further comprising a step of displaying on said display means the source data linked to when the image data displayed is

20   designated by designating means on the screen.

14. An object display method according to claim 13, further comprising a step of making said display means display the image data together with the window, of which a frame size

25   differs corresponding to a capacity of the source data to which the image data is linked.

15. An object display method according to claim 13, further comprising a step of making said display means display the image data together with the window of which a frame configuration differs corresponding to the number of hours or

5   days since the time when the source data to which the image data is linked was acquired.

16. An object display method according to claim 12, further comprising a step of displaying in movement plural

10   pieces of image data corresponding to respective pieces of source data in predetermined areas.

17. An object display method according to claim 12, further comprising:

15   a step of selecting a desired piece of image data from the image data displayed in movement; and

a step of displaying the selected image data in an area excluding the display area.

20   18. An object display method according to claim 17, further comprising a step of displaying the source data linked to on said display means when the image data displayed is designated.

25   19. A readable-by-computer recording medium stored with a program, for execution, comprising:

a step of converting a representative character string

of source data containing character strings into image data defined as an object;

a step of storing the source data and the image in a manner of relating these pieces of data to each other; and

5   a step of displaying the image data on display means.

20. A readable-by-computer recording medium stored with a program according to claim 19, further comprising a step of displaying on said display means the source data linked to when

10   the image data displayed is designated by designating means on the screen.

21. An object display device according to claim 1, further comprising a set means for setting an effective period as

15   attribute information with respect to the source data,

wherein said converter means for conversion into the image data does not convert the source data with an elapse over the effective period into the image data.

20   22. An object display device according to claim 2, wherein the previous image data is not displayed when the source data is displayed on said display means upon the designation of the image data.

25   23. An object display device comprising:

a display means for displaying plural pieces of information in a manner of sequentially changing a display

content;

a detect means for detecting a predetermined user's operation for the information displayed; and

a record means for recording the information operated in
5   accordance with the detection of the users' operation.

24. An object display device according to claim 23, wherein the plural pieces of information are displayed in movement in predetermined display areas.
10

25. An object display device according to claim 23, wherein the information is displayed in a predetermined display format on said display means as the record of the information.

15   26. An object display device according to claim 23, wherein the operation is a drag-and-drop operation aiming at a desired piece of information.

27. An object display device according to claim 23,
20   further comprising:

the detect means for detecting a selection indicating operation with respect to the information recorded; and

the display means for displaying linked information corresponding to the information subjected to the selection
25   indication operation.

28. An object display device according to claim 27,

wherein the linked information is source data, and

said object display device further comprises means for creating the information displayed by an extraction from the source data.

29. An object display device according to claim 28, wherein the source data belongs to a remote terminal connected via a network.

30. An object display method comprising:

a step of displaying plural pieces of information in a manner of sequentially changing a display content;

a step of detecting a predetermined user's operation for the information displayed; and

a step of recording the information operated in accordance with the detection of the users' operation.

31. An object display method according to claim 30, wherein said step of displaying the plural pieces of information includes a step of displaying the information in movement in predetermined display areas.

32. An object display method according to claim 30, wherein said step of recording the information includes a step of displaying the information in a predetermined display format on said display means.

33. An object display method according to claim 30, wherein the operation is a drag-and-drop operation aiming at a desired piece of information.

5   34. An object display method according to claim 30, further comprising:

a step of detecting a selection indicating operation with respect to the information recorded; and

a step of displaying linked information corresponding to

10   the information subjected to the selection indication operation.

35. An object display method according to claim 34, wherein the linked information is source data, and

15   said object display method further comprises a step of creating the information displayed by an extraction from the source data.

36. An object display method according to claim 35,

20   wherein the source data belongs to a remote terminal connected via a network.

37. A readable-by-computer recording medium recorded with a program, to be executed by a computer, comprising:

25   a step of displaying plural pieces of information in a manner of sequentially changing a display content;

a step of detecting a predetermined user's operation for

the information displayed; and

a step of recording the information operated in accordance with the detection of the users' operation.

5   38. A readable-by-computer recording medium recorded with a program according to claim 37, wherein said step of displaying the plural pieces of information includes a step of displaying the information in movement in predetermined display areas.

10

39. A readable-by-computer recording medium recorded with a program according to claim 37, wherein said step of recording the information includes a step of displaying the information in a predetermined display format on said display
15   means.

40. A readable-by-computer recording medium recorded with a program according to claim 37, wherein the operation is a drag-and-drop operation aiming at a desired piece of
20   information.

41. A readable-by-computer recording medium recorded with a program according to claim 37, further comprising:
a step of detecting a selection indicating operation with
25   respect to the information recorded; and
a step of displaying linked information corresponding to the information subjected to the selection indication

operation.

42. A readable-by-computer recording medium recorded
with a program according to claim 41, wherein the linked

5   information is source data, and

said program further comprises a step of creating the
information displayed by an extraction from the source data.

43. A readable-by-computer recording medium recorded

10 with a program according to claim 42, wherein the source data
belongs to a remote terminal connected via a network.

Abstract

An on-disk-top information display system enabling a user to visually easily grasp a content of information and capable of attaining a method of conceptually easily acquiring the
5   information, is disclosed. A representative character string is converted from source data including character strings into image data defined as an object, and the image data is displayed on a disk top. When the image data is designated, the source data linked to the image data concerned can be accessed. The
10   image data as the object representing the source data is displayed on a display screen, whereby a content of the source data can be grasped at a glance. This facilitates a user's judgement as to whether details of the source data should be browsed or not.

DISPLAY
DEVICE ⟋ I

2

DISPLAY
CONTROL
UNIT

DATE/TIME
MANAGEMENT UNIT

4

STORAGE
DEVICE ⟋ 3

FIG. 1

FIG. 2

FIG. 3

News: USA TODAY Latest news
USA Today[Sports] Date 08/07/1998

13
12
} 14

FIG. 4

News:USA TODAY Latest news
USA Today[Sports] Date 08/07/1998

13
12
} 14

FIG. 5

News:USA TODAY Latest news
USA Today[Sports] Date 08/07/1998

13
12
} 14

FIG. 6

News: USA TODAY Latest news
USA Today[Sports] Date 08/07/1998

13
12
} 14

FIG. 7

Ticker

| 10 | 11a | 11b | 11c |

Assistant | defeat Mets | News:USA TODAY Latest news | News
Menu | 8-5[8/04/1998] | USA Today[Sports] Date 08/07/1998 | Collage

Link Information (file, URL)

Information Type

Information Source

Information Title

Acquisition Date

Information Quantity

Sticker List

Link Information (file, URL)

Information Type

Information Source

Information Title

Acquisition Date

Information Quantity

Drag & Drop, etc

14

Sticker

News: USA TODAY Latest news
USA Today[Sports] Date 08/07/1998

FIG. 8

Sticker

News: USA TODAY Latest news — 13
USA Today[Sports] Date 08/07/1998 — 12 } 14

FIG. 9

FIG. 10

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名が発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

INFORMATION PROCESSING APPARATUS,

INFORMATION PROCESSING METHOD AND

MEDIUM

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ ＿月＿日に提出され、米国出願番号または特許協定条約国際出願番号を＿＿＿＿＿＿＿とし、（該当する場合）＿＿＿＿＿＿＿に訂正されました。

☒ was filed on _September 22, 1999_
as United States Application Number or
PCT International Application Number
PCT/JP 99/05202 and was amended on
＿＿＿＿＿＿＿ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第３７編第１条５６項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration
（日本語宣言書）

私に、米国出典第３５編１１９条(a)-(d)又は３６５条 (b) 項に基き下記の、米国以外の国の少なくとも一ヵ国を指定している特許協力条約３６５ (a) 項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)
外国での先行出願

			Priority Not Claimed 優先権主張なし
10-271952	Japan	25/09/1998	☐
(Number) （番号）	(Country) （国名）	(Day/Month/Year Filed) （出願年月日）	
(Number) （番号）	(Country) （国名）	(Day/Month/Year Filed) （出願年月日）	☐

私に、第３５編米国法典１１９条(e) 項に基いて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.) （出願番号）	(Filing Date) （出願日）

私は、下記の米国法典第３５編１２０条に基いて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約３６５条(c)に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第３５編１１２条第１項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願者提出日以降で本出願者の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第３７編１条５６項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.) （出願番号）	(Filing Date) （出願日）	(Status: Patented, Pending, Abandoned) （現況：特許許可済、保護中、放棄済）
(Application No.) （出願番号）	(Filing Date) （出願日）	(Status: Patented, Pending, Abandoned) （現況：特許許可済、保護中、放棄済）

私に、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じるところに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第１８編第１００１条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は其に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration
（日本語宣言書）

委任状： 私は下記の発明者として、本出願に関する一切の
手続きを米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。（弁護士、または代理
士氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor. I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith *(list name and registration number)*

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, P-41,455 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先： （名前及び電話番号）

Direct Telephone Calls to: *(name and telephone number)*

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor Takeshi KUMAZAWA
発明者の署名　　　　日付	Inventor's signature *Takeshi Kumazawa*　Date June 23, 2000
住所	Residence Kawasaki-shi, Kanagawa, Japan
国籍	Citizenship Japanese
私書箱	Post Office Address c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan
第二共同発明者	Full name of second joint inventor, if any Nobuhito FUKUI
第二共同発明者　　　日付	Second inventor's signature *Nobuhito Fukui*　Date June 23, 2000
住所	Residence Inagi-shi, Tokyo, Japan
国籍	Citizenship Japanese
私書箱	Post Office Address c/o Fujitsu Personal Computer Systems Limited, 1405, Ooaza Oomaru, Inagi-shi, Tokyo 206-0801, Japan

（第三以降の共同発明者についても同様に記載し、署名をすること）

(Supply similar information and signature for third and subsequent joint inventors.)